


Sommaire

- INTRODUCTION
- SCARAB INSTRUMENT STABILITY
- FIRST APPROACH
- IMPROVEMENT OF THE COLOCATION METHOD
- CONCLUSION





INTRODUCTION – CONTEXT





INTRODUCTION - DIFFICULTY







INTRODUCTION – ERROR BUDGET

ScaRaB-SW error budget @ $1\sigma \approx 1,6\%$

Items	Value	Туре	
Short wave calibration (sphere)	3% @2σ	Biais	1.5%
Error on spectral response		Biais	0.4%
Thermal gain correction	0.08%/°	Random	0.03%
	dT= 0.04° @1σ 20% of the thermal		
Thermal leak correction	leak@1σ	Random	0.04%
Location	0.06°@1σ	Random	0.4%
Budget at 1 sigma			1.6%

Rosak et al., 2012

CERES-FM2-SW error budget @ $1\sigma \approx 1\%$


	Bias errors of unknown sign (W m ⁻²)				
Source	Incoming solar	Outgoing SW	Outgoing LW	Net incoming	Comment
Total solar irradiance	±0.2	0	0	±0.2	Absolute calibration (95% confidence)
Filtered radiance	0	±2.0	±2.4 (N) ±5.0 (D)	±4.2	Absolute calibration (95% confidence)
Unfiltered radiance	0	±0.5	±0.25 (N) ±0.45 (D)	±1.0	Instrument spectral response function Unfiltering algorithm

Loeb et al., 2009 [CERES-FM2 error budget @2σ]

They showed that their error budget was consistent with the climate monitoring.




SCARAB INSTRUMENT STABILITY – RELATIVE GAINS






SCARAB INSTRUMENT STABILITY – MONITORING OF C1








$\theta = 1$, $\gamma = 1$ et $d\phi = 2$
θ = 2, γ = 2 et $d\phi$ = 5
$\theta = 5$, $\gamma = 5$ et $d\phi = 10$

	Compariso ΔA_k	n=
Measured TOA reflectance for Reference Sensor	Measured TOA reflectance for Sensor 2	Computed TOA reflectance for Sensor 2
Inverse radiative transfer (atmospheric correction)	TOA	Direct radiati transfer
Surface reflectance for reference sensor	SURFACE	Surface reflectance for sensor 2
	Spectral interpolation	

Trip	let	1-1-2	2-2-5	5-5-10
MERIS	N	119	1321	16724
	Ratio	0.9862	0.9870	0.9854
MODIS	N	246	2122	27016
	Ratio	1.0370	1.014	1.012



SCARAB INSTRUMENT STABILITY – APRIME COEFFICIENT






FIRST APPROACH: METHODOLOGY

To project CERES pixels onto ScaRaB pixel, several steps are necessary:

- 1- We define the colocation area between the two instruments to reduce computing time.
- **2-** ScaRaB footprint is about 40 km x 40 km at Nadir. We need to over-sample this pixel to project CERES pixel onto it.
- **3-** We locate the nearest CERES pixel of the ScaRaB sub-pixel (over-sampled).
- **4-** Each CERES pixel projected onto ScaRaB sub-pixel is defined by new coordinate. We use the latter to project CERES radiances.






FIRST APPROACH: SELECTION OF CERES PIXELS

To select a CERES pixel onto ScaRaB pixel we apply several criteria:

- ❖ Acquisition time difference lower than 5 minutes
- Conical aperture with an aperture of 5 degrees (solar & viewing angles)
- Occupation threshold (lowest number of CERES pixel onto ScaRaB sub-pixel)
- Heterogeneity threshold of CERES pixels (onto ScaRaB sub-pixel) lower than 10 %


NB: For k=10, occupation threshold is set to 10



 $\frac{ScaRaB - CERES}{mean(CERES)}$ (in %)





FIRST APPROACH: RESULTS - COLOCATION AREA







FIRST APPROACH: RESULTS – CAMPAIGN OF 2012















FIRST APPROACH: RESULTS - CAMPAIGN OF 2015













IMPROVEMENT OF THE COLOCATION METHOD


In our first colocation approach we considered a **circular** CERES *footprint* with a **20 km** diameter (at Nadir). It was a good approximation. In order to improve our results, we need to consider the real CERES *footprint*.





IMPROVEMENT OF THE COLOCATION METHOD






To improve our colocation method, we considered three kinds of improvements:

- 1. We consider the **real** CERES footprint (left caption).
- 2. The **entire** CERES footprint (cyan) must be contained in the ScaRaB footprint (left caption).
- 3. We **only** considered ScaRaB pixels which present radiometric homogeneity (right caption) neighbors heterogeneity (red) is lower than 10 %.




SECOND APPROACH: RESULTS FOR SW





SECOND APPROACH: RESULTS FOR LW





SECOND APPROACH: IMPACTS

Impact of the colocation method on the relative difference between CERES and ScaRaB:

❖ For SW

- In 2012: 0.9 % => 5.24 %
- In 2015: 1.94 % => 4.49 %

For LW

- In 2012: -0.72 % => -0.91 %
- In 2015: -0.89 % => -1.08 %

Impact of the colocation method on the dispersion of the relative difference between CERES and ScaRaB:

For SW

- In 2012: 9.2 % => 3.36 %
- In 2015: 11.75 % => 5.13 %

❖ For LW

- In 2012: 2.66 % => 1.38 %
- In 2015: 3.23 % => 1.14 %



CONCLUSIONS

- ❖ Taking account of the real CERES *footprint* improves inter-sensor calibration results.
- ❖ Best results are obtained using homogeneous ScaRaB pixel containing the entire CERES footprint.
- ❖ For SW, we note a degradation of the results between 2012 and 2015.

